



Cold Kitchen Equipment



Hot Kitchen Equipment



Food Process Equipment



Beverage Equipment



About Us

Heat Kitchen Equipment is a Malaysia Based Food Service Equipment Distributor and Supply Company Established in 2017 ,15 year Experience in this industrial. We Specialised in Quanlity Kitchen and bar Equipment and Stainless Steel Design and Fabrication ,Project Management and implementation ,Consider a 4S company,SALES ,SERVICE,SPARE PART and SUPPORT .

medium and high range.

Our Target is Supply the suitable kitchen and bar Equipment to our Clients and Propose new Technologies Kitchen Equipment for Ours Client to Solve the operation Problem and Man power cost save solution ,Cost Reducer and Business Expanding Solution for Chain Store ,QSR, back up support service support is our goal.

We provide kitchen Design build and set up for Restaurant ,Cafe ,food court ,Hotel,Beverage bar ,central kitchen

Food service Consultation ,Kitchen solution ,Smart Kitchen Work Flow Consult,Kitchen equipment preventing maintainance



HOT KITCHEN




HAUSCOOK IH COOKER

- Dimensions : 490L x 230W x 410H mm
- Power Supply : 220 V - AC 50 / 60 Hz / 1 / 25 amps
- Rated Power : 1.7 Kw
- Tank Capacity : 1.5 Liter
- Weight : 4.5 Kg
- Heating Type : Hot Water Tank Type
- Cooking Type : Available for cooking both general and instant
- Connecting Water : Apart from running water, water pail can be used as pump
- Filtration feature : Filtered water can be used by installation of water filter

Benefits

- The time for cooking can be reduced because of its high thermal efficiency.
- Consumption of electricity is reduced (cost-saving).
- Users are safe from the risk of fire or skin burns.
- It is eco-friendly because it does not emit harmful gases.



The machine which come with build in water filter and hot water tank ,auto refill ,3 memory to set time and dispenser water level ,cook and dispenser water same time ,for a korean noodle cooking time 3.5 minute ,water temperature are 85c .



Used daily, VITO filters remove food particles and carbon from your frying oil. Frying in clean, filtered oil will result in a better tasting and better looking fried product. Your oil costs will be cut and there will be less workload due to less changes of oil and cleaning.



The FT 440 provides easy measurement and saves oil.

- Measure the quality and temperature of your oil
- Change your oil at the right time
- Quick and reliable measuring results
- Supports HACCP quality standards
- Ergonomic and sturdy design
- High degree of protection (IP67)



- Increases the lifetime of your oil
- Improves taste and quality
- Saves time and labor






The VITO XM cleans the oil, stores it in its 137 lbs tank and provides an easy and hygienic transport in the kitchen. Because of its innovative vacuum-filtration technology, particles remain in the filter in a dry condition. Like every VITO oil filter system the XM provides a microfiltration up to 200 μ m. The unique design makes sure the XM can handle temperatures up to 392°F and provides highest safety at work, because of avoiding direct contact with the hot oil. After filtration the oil can easily be pumped back into the fryer automatically

24" GAS GRIDDLE

PBT24-0-24G-A

- 2 x 30,000 BTU U style burner
- 0.75" thickness griddle plate
- 2 independent gas valve control
- Zinc alloy material knobs
- 4" adjustable stainless steel feet
- 1 pull-out waste tray
- All stainless steel construction
- 3/4" rear gas connection
- Include conversion orifices
- ETL&NSF approval



POWERLINE EQUIPMENT COMPANY



Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480

www.powerlineequip.com



6 BURNER 36" COUNTERTOP RANGE PBT36-6-A

- 6 x 25,000 BTU manually controlled burner
- Heavy duty cast iron & removable grate
- 6 independent gas valve control
- Zinc alloy material knobs
- 4" adjustable stainless steel feet
- 1 pull-out waste tray
- All stainless steel construction
- 3/4" rear gas connection
- Include conversion orifice kit
- ETL&NSF approval



POWERLINE EQUIPMENT COMPANY



Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480

www.powerlineequip.com



4 BURNER 24" RANGE WITH STANDARD OVEN PBR24-4-A

- 4 x 30,000 BTU open top burners
- 30,000 BTU standard oven
- 12" x 12" heavy-duty cast iron grates
- 4 3/4" deep back shelf and 2" front ledge
- 6" adjustable stainless steel legs
- 2 nickel-plated metal oven racks and 4 positions
- 3/4" gas inlet pipe
- 1 pulled-out crumb tray
- Rugged stainless steel front and aluminium sides
- Zinc alloy material knobs
- 250-550 degrees Fahrenheit for oven temperature
- Chamber interior size: 20 5/8" W x 25 7/8" D x 13 7/8" H
- ETL&NSF approval



POWERLINE EQUIPMENT COMPANY


Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480

www.powerlineequip.com



4 BURNER 24" COUNTERTOP RANGE PBT24-4-A

- 4 x 25,000 BTU manually controlled burner
- Heavy duty cast iron & removable grate
- 4 independent gas valve control
- Zinc alloy material knobs
- 4" adjustable stainless steel feet
- 1 pull-out waste tray
- All stainless steel construction
- 3/4" rear gas connection
- Include conversion orifice kit
- ETL&NSF approval



POWERLINE EQUIPMENT COMPANY

Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480



www.powerlineequip.com



COUNTER-TOP CHARBOILER WITH LAVA ROCK

PBB24-A

- Made of high-quality stainless steel, this product is corrosion resistant, rustproof and permits easy removal of cooking fumes.
- The one stretch forming worktop is tough, tenacious and simple. It is also smooth and flat so that it will not collect dirt and can be completely cleaned.
- With an efficient heating tube, this product is energy-saving and efficient and ensures safety and convenience. Free temperature setting is available. *Users can adjust the cooking temperature as they want to meet the temperature requirements for cooking different food.
- The oil basin can collect the oil conveniently to keep it clean and efficient.



Model		PBB24-A
Dimension (mm)		600 x 650 x 475
Height of Working Table (mm)		335
LPG	Pressure (Pa)	2800
	Power (kW)	14.4
	Gas Cons. (kg/h)	1.2
NG	Pressure (Pa)	2000
	Power (kW)	14.4
	Gas Cons. (m ³ /h)	1.52
Temperature (°C)		120-200
Gas Inlet Size		R 1/2"
Weight (kg)		67

POWERLINE EQUIPMENT COMPANY



Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480

www.powerlineequip.com



6 BURNER 36" RANGE WITH STANDARD OVEN PBR36-6-A

- 6 x 30,000 BTU open top burners
- 30,000 BTU standard oven
- 12" x 12" heavy-duty cast iron grates
- 4 3/4" deep back shelf and 2" front ledge
- 6" adjustable stainless steel legs
- 2 nickel-plated metal oven racks and 4 positions
- 3/4" gas inlet pipe
- 1 pulled-out crumb tray
- Rugged stainless steel front and aluminium sides
- Zinc alloy material knobs
- 250-550 degrees Fahrenheit for oven temperature
- Chamber interior size: 26 7/8" W x 25 7/8" D x 13 7/8" H
- ETL&NSF approval



POWERLINE EQUIPMENT COMPANY

Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480

www.powerlineequip.com



#304 Stainless steel interior & exterior. Ultra low energy consumption with a thermostatic control. One (1) single compartment and one (1) temperature control with two (2) doors to preserve the heat and prevent the heat from escaping fast when a door needs to be opened. Zero ODP injected polyurethane insulation for environmental protection. Factory preset temperature to operate between 76°C and 86°C to have a better control on temperature while having rooms for a possible adjustment of temperature within in a safe temperature range. Electronic controller with a LCD display. Safety cut out switch – heated. Color-coded control panel (in red color for the heated cabinets) for easy identification of the nature of the cart. Interior curved corners/edges for easy cleaning and hygiene & sanitation purposes. Gastronorm shelving system with anti-tilt slides. Mechanical parts are easily accessible for quick servicing & maintenance. Two (2) sets of stylish and robust door handles on each side of the cart for easy transportation. Two (2) lockable self-closing doors. Door handles are equipped with lock. Four (4) heavy-duty casters; two (2) swivel and two (2) with brake. Full-perimeter bumper guard to ensure heavy duty use and protection.



#304 Stainless steel interior & exterior. Bottom-mounted high ambient 43°C refrigeration system, using R134a refrigerant, generating 1584 BTU (399 Kcal) per hour. Ultra low energy consumption. Zero ODP injected polyurethane insulation for environmental protection. Factory preset refrigerator temperature at -2 / +4°C. Electronic controller with a large LCD display. Audio visual temperature alarms come as standard, along with HACCP capability. Automatic defrost (hot gas defrost – refrigerator) to help minimizing service needs.



CHEFTOP MIND.Maps™ PLUS COUNTERTOP

Combi oven 5 GN 1/1

Oven model: **XEVC-0511-EPRM**

Tray pitch: 67 mm

Voltage: 380-415V3N~

|220-240V3~|/9,3 kW

Dimensions - w x d x h: 750 x 783 x 675 mm

Weight: 70 kg

Opening type: Hinge on the left side



CHEFTOP MIND.Maps™ PLUS COUNTERTOP

Combi oven 3 GN 1/1

Oven model: **XEVC-0311-EPRM**


Tray pitch: 67 mm

Voltage: 380-415V 3N~ | 220-240V 3~ | 220-240V 1N~/5KW

Dimensions: 750 x 783 x 538 mm

Weight: 56 kg

Opening type: Hinge on the left side





UNOX LINEMISS CONVECTION OVEN MODEL:XFT-133

Pitch:75 mm

Frequency:50 / 60 Hz

Voltage:230V 1N~

Electrical power:3 kW

Dimensions WxDxH (mm)

600x655x509

Weight:31 kg

Humidity:YES



UNOX LINEMISS CONVECTION OVEN MODEL:XF-023

Pitch:75 mm

Frequency:50 / 60 Hz

Voltage:230V 1N~

Electrical power:3 kW

Dimensions: WxDxH(mm):600x587x472MM

Weight:22 kg



ROLLER GRILL ELECTRIC GRIDDLE

- Outside Dimensions : 900x475x230mm
- Cooking surface : 900x400mm
- Cooking area : 3
- Power : 3 x 3 kW (3 Cords)
- Volts : 380 V
- Weight : 44Kg



ROLLER GRILL ELECTRIC GRIDDLE

- Outside Dimensions : 600x475x230mm
- Cooking surface : 600x400mm
- Cooking area : 2
- Power : 6.4Kw
- Weight : 32Kg



HEAT ELECTRIC GRIDDLE

- Outside Dimensions : 650x580x340mm
- Cooking surface : full flat
- Cooking area : 2
- Power : 5Kw
- Volts : 220-240 V
- Weight : 34Kg





MEDIUM DUTY MICROWAVE OVEN 1100W RCS511TS

- Dimensions : 483Dx559Wx352H mm
- Power Supply : 230V / 50 Hz, 13 A single phase
- Frequency : 2450 MHz, 1100 watts of cooking power.



HEAVY DUTY MICROWAVE OVEN 1800W DEC18MU

- Dimensions : 574D x 419W x 343H mm
- Power Supply : 230 V / 50 Hz, 13 A single phase
- Power Output : 1900 W
- Power Consumption : 2900 W, 12.6 A ,



MENUMASTER XpressChef™ 3i Series Speed Oven

- Dimensions : 743D x 358W x 578H
- 4000 or 5000 watts of power
- Temperature Range : 95° - 270°C (200° - 520°F)
- Exterior Finish : Stainless steel and Painted Steel
- Power Level : 11
- 2 Magnetron : 61kg / 1 Magnetron : 53kg

MENUMASTER®
Commercial



WISE COMMERCIAL RICE COOKER/WARMER

Product Name

Electronic Rice Cooker / Warmer

Model:CFXB138-195XG-A

Dimensions (W x D x H):455 x 390 x 340(mm)

Power:110V / 220V 1.95KW

Capacity:13L

Temp.Range:50-150°C

60
Cup
(14 Liter)



RINNAI 10 LT GAS RICE COOKER

SPECIFICATIONS


Gas Connection	9.5
Gas Consumption (LPG)	7.95
Product Weight (Kg)	15
Product Size (WxH)mm	531 x 420



DESIGNED FOR
YOUR OWN TASTE

RINNAI GAS SALAMANDER-6
BURNERS

Model	RGP-46A
Dimensions (LxWxH) mm	978 x 400 x 602
Weight (Kg)	35
Gas Connection	9.5
Type of Gas	Please Ijdicate LP Gas or Natural Gas



This compact yet powerful snacking grill is perfect for toasting, grilling and re-heating sandwiches and snacks of all kinds, including Pizza, Croque-Monsieur, Quiches and toasts. Heating from top and bottom the BAR1000 is a high speed toaster or it can be used as a traditional salamander by just using the top elements. With a heat up time of 30 seconds the BAR1000 is an efficient cooking platform and the radiant infrared technology keeps

ROLLER GRILL BAR1000	
Weight	10Kg
Dimensions (mm)	450 x 285 x 305
Element Type	Quartz / Infrared
Power	2 Kw
Shelf Area	350 x 250



4HS
2



RCTHW-6
W/Steamer Plate
Adapter



4HS

Model	Power	Outside Dimensions	Weight	Volts
RCTHW-6	6 Kw	610 x 368 x 282mm	14Kg	220 V /50/1
4HS2	4Kw	475 x 475 x 130mm	9Kg	220 V /50/1
4HS	4Kw	475 x 475 x 130mm	9Kg	220 V /50/1



-MODEL : RCTHW-6 w/Soup Kettle Adapter And Two 7 Liter Soup Pans w/Lids

- Dimension : 368Wx610Dx282Hmm
- Voltage : 220/50Hz/Single Phase



-MODEL : RCTHW-6 w/Sauce Kettle Adapter And Three 4 Liter Sauce Pans w/Lids

- Dimension : 368Wx610Dx282Hmm
- Voltage : 220/50Hz/Single Phase



- MODEL: RHW-2

- INCLUDES TWO WELLS WITH 10 LITER POTS AND HINGED LIDS
- Dimension: 630Wx330Dx355Hmm
- Volatage : 230Vols/50Hz/Single Phase



- MODEL : RCTHW-6 w/Standard Pasta Cooker Adapter And Optional Stainless Steel Noodle Ladles

- Dimension : 368Wx610Dx282Hmm
- Voltage : 220/50Hz/Single Phase



Lestov

Commercial Induction Hob Manufacturer

- ★ 18 years of manufacturing experience
- ★ Full range of catering equipment
- ★ Independent R&D/design/production
- ★ Customized OEM+ODM



Lestov



EQUIPMENT/QUICK SERVING RESTAURANT

Company Profile

The foundation of every WISE product is well-defined and customer-oriented. We are the manufacturer and trade company through 35 years experience of development, together with top-notch technology and complete after-sales service network. WISE has two extensive lines of electric kitchen equipment and commercial restaurant refrigeration. In order to follow the ever-changing trend, our company strives to reach the goal to 'Wise your kitchen' to sincerely serve our valued customers. In addition, we welcome all kinds of feedback and suggestion for mutual understanding and further cooperation. The future of culinary world lies in the hand of young generations and the journey starts from a well-equipped kitchen environment. It is such an honor for WISE to be part of the journey.



Production Line

Guangzhou, Foshan factory implements precise and normative management to ensure our quality of products



ISO/CE Certificates & Patents

ISO/CE Certificates & Patents Company is attested by both ISO9000:2000 & CE in order to meet customers' needs satisfactorily by our exclusive products & services.



Our Craftsmanship

Take one look at WISE products and you know it has been well-crafted. The intricate details, perfected joints and unique design features are just a few giveaways, but it is also its durability that completes your commercial kitchen and its unique style. Above all, the traditional methods we use to craft your ideal commercial kitchen equipments are what WISE pride ourselves on. We have established a highly regarded balance between new and exciting product innovations and good old-fashioned craftsmanship by applying both mechanical and manual way to make sure every product is produced in a refined fashion.





WISE PAU STEAMER MACHINE (U-SHAPE)

4 SPEACIAL 4 FEATURES

A.Special designed indicator light to prevent heater from dry heating without water filling.

B.Heating indicator light helps monitor internal temperature.

C.German EGO thermostat controls temperature

D.Special designed heating device to enable the heating time adjustable



Wise curve Glass Warmer showcase

model:WHS-590C

Dimension:590x420x726mm

Capacity:113L

Power:220v/50hz/800w/13amps

Temp:85~99

WISE®



Standing Electric Fryer



WEL-1L



WEL-2L



WEL-3L

FEATURES

- Digital control system with one-button-pressing for automatic frying operation.
- Each tank is able to set 6 different kinds of food's timing from its respective channel and can work simultaneously.
- Easy frying by independent control panel with 12-channel timer.
- Built-in overheat protection device for safety. When oil temperature exceeds the set temperature, the power will be cut off. (Manual restoration).
- Easy cleaning with lift-up heating element.
- Use "all-in-one-button" frying operation program, frying basket will lift up automatically. This function is especially efficient for user during rush hours to avoid improper frying time. (For the fryer with auto lift-up system only)

Detail Description



12 pre-set cooking program



U-shape stainless steel heat exchanger tube



Automatic basket lift up



Filtration

Product Name	28L Electric Standing Fryer	56L Electric Standing Fryer	84L Electric Standing Fryer
Model	WEL-1L	WEL-2L	WEL-3L
Capacity	28L	28L*2	28L*3
Dimension(W*D*H)	400*800*935/1160(mm)	800*800*935/1160(mm)	1200*800*935/1160(mm)
Power	3N~380V 50Hz 14kW	3N~380V 50Hz 14kW*2	3N~380V 50Hz 14kW*3
Temp. Range	Room Temp. to 190°C	Room Temp. to 190°C	Room Temp. to 190°C

Product Name	28L Electric Standing Fryer (twin tanks)	28L Electric Standing Fryer with Filtration	28L Auto Lift-Up Electric Standing Fryer	Auto Lift-Up Electric Standing Fryer with Filtration
Model	WEL-1L-2	WEL-1LF	WELL-1L	WELL-1LF
Capacity	28L	28L	28L	28L
Dimension(W*D*H)	400*800*935/1160(mm)	400*800*935/1160(mm)	400*915*935/1464(mm)	400*915*935/1464(mm)
Power	3N~380V 50Hz 7kW*2	3N~380V 50Hz 14kW	3N~380V 50Hz 14kW	3N~380V 50Hz 14kW
Temp. Range	Room Temp. to 190°C	Room Temp. to 190°C	Room Temp. to 190°C	Room Temp. to 190°C

Holding Cabinet (Pass-Through Counter Type)

FEATURES

- LED digital display clearly indicates parameter for easy reading.
- Built-in microcomputer controller to set temperature respectively for each layer and independent power switch for each layer saves power consumption cost by turning off switch for layer not being used.
- Each layer (front and back) is equipped with 2 independent timers to set warming time between 1 second to 99 minutes 59 seconds for different kinds of foods. Each time controller will not affect other timers' operation. Special design for crispy or moist food by different layer storage.
- Alarm alert gives signal to remind warming time.
- WTC heat patch and aluminum heating plate make heating evenly and constant to efficiently save power consumption up to 30%.
- Front and back pass-through food access with timer indicating the same warming time.
- Heat tolerance is up to 190°C, securing food safety.
- Durable stainless steel body is easy to clean.



WHS-790-2



WHS-520-4

Product Name	4-Layer Holding Cabinet (Pass-Through Counter Type)	2-Layer Holding Cabinet (Pass-Through Counter Type)
Model	WHS-520-4	WHS-790-2
Dimension(W*D*H)	515*630*680(mm)	790*400*320(mm)
Power	220V 50Hz 3.5kW	220V 50Hz 1.8kW
Capacity	4Layers	2Layers
Temp. Range	Room Temp. to 100°C	Room Temp. to 100°C

Holding Cabinet

FEATURES

- Hot air circulation enables heat to be distributed to every corner of the cabinet and maintains good thermal balance.
- It can store foods in the high temperature in batches. Enhance the efficiency of food preparation in commercial kitchens.
- Good maintenance of humidity inside the cabinet keeps food moist and fresh for longer time.
- Maintaining high temperature prevents bacteria growth and keeps food safe to consume to meet the HACCP requirement.
- Depending on usage or location, front open door or pass-through door can be selected for easy food storage.
- Optional casters available.



WHT-1140-1D
WHT-1140-2D



WHT-1940-2D
WHT-1940-4D

Product Name	1140mm Heated Holding Cabinet (One Door)	1140mm Heated Holding Cabinet (Two Door pass through)	1940mm Heated Holding Cabinet (One Door)	1940mm Heated Holding Cabinet (Two Door pass through)
Model	WHT-1140-1D	WHT-1140-2D	WHT-1940-2D	WHT-1940-4D
Dimension(W*D*H)	710*780*1140(mm)	710*780*1140(mm)	710*780*1940(mm)	710*780*1940(mm)
Power	220V 50Hz 1.8kW	220V 50Hz 1.8kW	220V 50Hz 1.8kW	220V 50Hz 1.8kW
Capacity	240L	240L	540L	540L
Temp. Range	Room Temp. to 99°C	Room Temp. to 99°C	Room Temp. to 99°C	Room Temp. to 99°C

Milk Chiller

FEATURES

- The curve design makes the surface elegant and generous.
- With rounded corner inside, non-dead angle enables easy cleaning.
- High density polyurethane foam enable better insulation.
- Stainless steel structure makes it durable and easy to cleaning.
- Door rubber seal can be removable, easy to clean and change.
- Cooling speed is fast, perfectly keep cooling.

Product Name	Milk Chiller
Model	WRT-8L-R1
Dimension(W*D*H)	265*470*574(mm)
Capacity	8L
Power	110V 60Hz 176W/ 220V 60Hz 150W
Compressor Motor	1/11HP Motor
Temp. Range	2~6(°C)
Refrigerant	R134a
Cooling System	Air Cooling



Curved Glass Warmer Showcase

FEATURES

- Extra large design, super slim base, maximize the storage space.
- High heat conduction alumium heating board combines radiant heating and presents the best performance. Even temperature distribution within the space meanwhile preserve the humidity of food.
- Adopt special lighting makes the food look even more delicious.
- Professional and elegant design enhances the store image.
- Respective control of lighting and heating to satisfy different needs to precise control the temperature in the showcase.

Product Name	Curved Glass Warmer Showcase
Model	WHS-590C
Dimension(W*D*H)	590*420*726(mm)
Capacity	113L
Power	220V 50Hz 800W
Temp. Range	Room Temp. to 100°C





- *Model: CRWD500TP
- *Dimensions : 590x605x840mm / Basket Dimensions : 500x500mm
- *Capacity : 30Basket / hour
- *Weight : 61Kg
- *Electical Connection : 230v/50Hz
- *Total Power : 5.2Kw
- *Tank Heating Element : 3.0Kw
- *Boiler Heating Element : 4.5Kw
- *Wash Pump Power : 0.65Kw
- *Tank Capacity : 17Liters / Basket Plate Capacity : 18
- *Boiler Capacity : 6.2Liters
- *Washing Water Temp : 55C / Rinsing Water Temp : 85C
- *Package Dimensions : 600x700x950mm



- *Dimension: 55x62x140 cm
- *Net Weight: 220 Kg
- *Type: Wheeled
- *Production Capacity:Min: 2 – Max: 7 Lt/Cycle
- *Cylinder Capacity:Min: 1.5 – Max: 5 Kg
- *Condensation:Water / Air
- *Electronic Control:Touch Screen
- *Voltage: 400 V
- *Frequency: 50/60Hz
- *Power: 4.7kW






COLD KITCHEN



Commercial Chest Freezer

Flat Glass Sliding Lid Series - 250GL/ 350GL/ 450GL/ 600GL/ 750GL



www.snow.com.my

Model	UOM	LY 250 GL	LY 350 GL	LY 450 GL	LY 600 GL	LY 750 GL
Product Name		Freezer	Freezer	Freezer	Freezer	Freezer
External Dimensions						
W	mm	824	1049	1329	1659	2094
D	mm	662	662	662	662	662
H	mm	840	865	865	865	865
H1	mm	-	-	-	-	-
Internal Dimensions						
W	mm	695	920	1200	1530	1966
D	mm	530	530	530	530	530
H	mm	703	703	703	703	703
H1	mm	-	-	-	-	-
Total Capacity	L	230	320	420	540	710
Effective Capacity	L	190	260	360	460	600
Lid/door Type		Flat Glass Sliding Lid				
Power Consumption (24h at 30°C ambient)	kWh	2.7	3.2	4	4.4	5.3
Temperature range at 30°C ambient	°C	-18 -22	-18 -22	-18 -22	-18 -22	-18 -22
Net Weight	kg	50	58	75	87	112
Gross Weight	kg	60	70	91	109	137
Compressor Power	hp	1/5	1/4	1/3	1/3	3/8
Color		White	White	White	White	White

Outer Panel & Interior Cabinet

Mild steel and galvanised steel sheet
with epoxy powder coating

Evaporator & Condenser

Zinc coated Bundy tube

Insulation

Polyurethane foam, 60mm thick (CFC Free)
38mm thick for cooler

Refrigerant

R 134a (CFC Free)

Power Source

220-240v, single phase
50Hz.



Technical features may change without prior notice

COUNTERTOP CHILLER

RTW-100L-3/ RTW-160L-4

- Adjustable coated shelves
- Auto defrost function
- Digital thermostat & temperature display
- Hot air blowing glass door (Anti-Fog)
- Internal LED lighting on top 2 sides
- Maintenance free
- Simple construction and high security
- Ventilated cooling system

Model	RTW-100L-3	RTW-160L-4
Product Name	Chiller	Chiller
External Dimension <i>Length x Width x Height (mm)</i>	705 x 472 x 687	880 x 568 x 686
Capacity	100 Liters	160 Liters
Rate Input Power	190 W/ 195 W	230 W/ 160 W
Power Consumption <i>(30°C ambient)</i>	3.32 kWh / 24h	3.06 kWh / 24h
Refrigerant	R134a	
Temperature Range	2°C ~ 10°C	
Net Weight	39 kg	71 kg
Gross Weight	42.5 kg	73.5 kg
Comp. Power (Hp)	1/4	
Body Colour	Black	
Climate Class	4	


* Product specification are subject to change without prior notice.



RTW-100L-3



RTW-160L-4



TWO & THREE DOOR DISPLAY CHILLER/ FREEZER

LY1000BBC-H/ LY1000BBC-HB |
LY1500BBC-H/ LY1500BBC-HB

- Adjustable coated shelves
- Aluminium door frame
- Auto defrost function
- Better at retaining product temperature
- Digital thermostat & temperature display
- Energy saving
- Fin & coil with fan cooling system
- Heated tempered glass door
- Self-closing door
- Suitable for all usage



LY1500BBC-H/
LY1500BBF-H



LY1500BBC-HB/
LY1500BBF-HB



LY1000BBC-H/
LY1000BBF-H



LY1000BBC-HB/
LY1000BBF-HB

Model	LY1000BBC-H/ LY1000BBC-HB	LY1000BBF-H/ LY1000BBF-HB	LY1500BBC-H/ LY1500BBC-HB	LY1500BBF-H/ LY1500BBF-HB
Product Name	Chiller	Freezer	Chiller	Freezer
External Dimension <i>Length x Width x Height [mm]</i>	1240 x 735 x 2075		1846 x 735 x 2075	
Internal Dimension <i>Length x Width x Height [mm]</i>	1140 x 591 x 1370		1746 x 591 x 1370	
Capacity	923 Liters		1414 Liters	
Rate Input Power	700 W	1180 W	950 W	1850 W
Power Consumption <i>(30°C ambient)</i>	10.0 kWh / 24h	20.0 kWh / 24h	14.0 kWh / 24h	31.0 kWh / 24h
Refrigerant	R134a	R404a	R134a	R404a
Temperature Range	0°C ~ 10°C	-12°C ~ -18°C	0°C ~ 10°C	-12°C ~ -18°C
Net Weight	149 kg	185 kg	218 kg	276 kg
Gross Weight	154 kg	190 kg	226 kg	284 kg
Comp. Power <i>[Hp]</i>	3/8	1	1/2	1 1/2
Body Colour	White/ Black		White/ Black	
Coated Shelves	8 pcs		12 pcs	
Layer Heated Glass Door	Double	Triple	Double	Triple

* Product specification are subject to change without prior notice.

SINGLE DOOR DISPLAY CHILLER

LG-268F/ LG-350F

- Adjustable coated shelves
- Auto defrost function
- Auto water drains + self-evaporates
- Better at retaining product temperature
- Build in lock & key
- Digital thermostat & temperature display
- Energy saving
- Fin & coil with fan cooling system
- Hot air blowing glass door (Anti-Fog)
- Suitable for all usage

Model	LG-268F	LG-350F
Product Name	Chiller	Chiller
External Dimension <i>Length x Width x Height (mm)</i>	530 x 590 x 1845	620 x 630 x 1935
Internal Dimension <i>Length x Width x Height (mm)</i>	440 x 430 x 1225	530 x 473 x 1320
Capacity	268 Liters	350 Liters
Rate Input Power	210 W	255 W
Power Consumption <i>(30°C ambient)</i>	1.9 kWh / 24h	2.86 kWh / 24h
Refrigerant	R134a (CFC Free)	
Temperature Range	0°C ~ 10°C	
Net Weight	64 kg	75 kg
Gross Weight	72 kg	85 kg
Comp. Power <i>(Hp)</i>	1/6	1/4
Body Colour	White	
Coated Shelves	5 pcs	

* Product specification are subject to change without prior notice.



LG-268F

LG-350F



RT-78L(2R)



RT-78L-3



RT-215L-3

Model	RT-78L(2R)	RT-78L-3	RT-215-3
Product Name	Curved Glass Door	Flat Glass Door	Flat Glass Door
External Dimensions	429x425x980	452x406x966	556x526x1613
Gross Capacity (L)	86	78	215
Rated Input Power (W)	180	190	400
Refrigerant	R-134a	R-134a	R-134a
Temperature Range	0°C - 12°C	0°C - 12°C	2°C - 12°C
Class Mate	4	4	4
Net Weight (kg)	36.5	36	73.5
Special Features	- Front curved glass door	- Low energy consumption - Simple construction and high security - Air duct outside the glass to remove condensation water	

OPEN SHOWCASE CHILLER

RTS-360L/ RTS-390L

- Adjustable coated shelves
- Auto defrost function
- 4 castors with 2 brakes
- Condensation water evaporated automatically
- Digital thermostat & temperature display
- Filter mesh in front of the base
- Internal LED lighting on top and each shelf
- Maintenance free
- Side single tempered glass
- Ventilated cooling system
- With night curtain

Model	RTS-360L	RTS-390L
Product Name	Chiller	Chiller
External Dimension Length x Width x Height (mm)	876 x 945 x 1520	920 x 847 x 1510
Capacity	360 Liters	390 Liters
Rate Input Power	1400 W/ 1300 W	
Power Consumption (30°C ambient)	16.87 kWh / 24h	10.70 kWh / 24h
Refrigerant	R404a	
Temperature Range	2°C ~ 10°C	
Net Weight	125 kg	123 kg
Gross Weight	145 kg	143 kg
Comp. Power (Hp)	1/2	3/4
Body Colour	White	Black
Climate Class	6	



RTS-360L



RTS-390L

* Product specification are subject to change without prior notice.

62L Glass door mini fridge

- Dimensions : 410W x 465D x 640H mm
- Temperature Range : 0 ~ 10°C
- Electrical : 220-240v / 50hz - 85 w
- Material : Color steel, polyurethane
- Led : White , With Lock



- An ideal choice for rec rooms, dorm areas, offices, and more.

95 L glass door mini fridge

- Size : 460W x 470D x 840H mm
- Temperature Range: 0~10°C
- Material: color steel, polyurethane
- Led/Lock: White/Yes
- Color: black
- Weight: 33kg



46 L glass door mini fridge

- Size : 410W x 465D x 480H mm
- Temperature Range: -3~10°C
- Material: color steel, polyurethane
- Led/Lock: White/Yes
- Color: black
- Weight: 23kg



2 Door Beer Cooler (Black)

900x 550x 860H mm
CAPA : 230L/ Temperated : 2~8°C
220v/ 50hz/ 1/ 200w/ 60kg
Packing Size : 940x 600x 910H mm




S series B type black bar freezer



- Automatic evaporation of condensed water ■ Refrigerant: R134a No Frost





MODEL	SHB-108LF
Temperature	Refrigeration (2~8°C)
Volume	108 L
Dimensions	W500*D550*H860mm
Power	220W



MODEL	SHB-230L2F
Temperature	Refrigeration (2~8°C)
Volume	230 L
Dimensions	W900*D550*H860mm
Power	285 W



MODEL	SHB-350L3F
Temperature	Refrigeration (2~8°C)
Volume	350 L
Dimensions	W1350*D550*H860mm
Power	385 W





Cube Ice Machine

CUBE ICE MACHINE

Under-Counter Type – Exclusive



MODEL	SK-51B	SK-81B	SK-101B
Ice Production	50kg / 24h	80kg / 24h	100kg / 24h
Ice Storage	30 kg	30 kg	30 kg
Power	465 w	660 w	660 w
Gross Weight	50 kg	65 kg	67 kg
Dimension	666 × 637 × 775 mm	666 × 637 × 775 mm	666 × 637 × 775 mm

Products Size (unit:mm)

140	30	25	0	666	637	775
140	30	25	0	666	637	775
140	30	25	0	666	637	775

Summary table

Model	Output 24hrs	Ice Storage	Power	Gross Weight	Net Dimension [Feet Included (W × D × H/mm)]
SK-51B	50 kg / 24 h	30 kg	465 w	50 kg	666 × 637 × 775 mm
SK-81B	80 kg / 24 h	30 kg	660 w	65 kg	666 × 637 × 775 mm
SK-101B	100 kg / 24 h	30 kg	660 w	67 kg	666 × 637 × 775 mm



06-07

CRESCENT



CRESCENT ICE MACHINE



MODEL	SK-220M	SK-280M
Ice Production	95kg / 24h	127kg / 24h
Ice Storage	40 kg	40 kg
Power	770 w	780 w
Gross Weight	70 kg	77 kg
Dimension	650 × 651 × 1063 mm	650 × 651 × 1063 mm

Products Size (unit:mm)

650	44	603	44	651	1063
650	44	603	44	651	1063
650	44	603	44	651	1063



MODEL	SK-320M	SK-620M
Ice Production	145kg / 24h	280kg / 24h
Ice Storage	125 kg	125 kg
Power	850 w	1800 w
Gross Weight	118 kg	131 kg
Dimension	583 × 830 × 1897 mm	583 × 830 × 1897 mm

Products Size (unit:mm)

583	830	1897	583	830	1897
583	830	1897	583	830	1897
583	830	1897	583	830	1897

Summary table

Model	Output 24hrs	Ice Storage	Power	Gross Weight	Net Dimension [Feet Included (W × D × H/mm)]
SK-220M	95 kg / 24h	40 kg	770 w	70 kg	650 × 651 × 1063 mm
SK-280M	127 kg / 24h	40 kg	780 w	77 kg	650 × 651 × 1063 mm
SK-320M	145 kg / 24h	125 kg	850 w	118 kg	583 × 830 × 1897 mm
SK-620M	280 kg / 24h	125 kg	1800 w	131 kg	583 × 830 × 1897 mm

Crescent Ice Machine

16-17

BEVERAGE EQUIPMENT





Heat Cups sealer machine
Double screen (Temp,Figure)
250x392x530mm
24KG
540-640cups/

FRUCTOSE MACHINE
Model : HLG9EN
Dimension : 210x370x450mm
Voltage : 220V/50Hz/1
Capacity : 7L
Second dispensugar syrup
Auto Lock Dispencer Hole
16 Button
304 Stainless Steel



BevGuard
FILTRATION SYSTEMS

SPEC SHEET

BGE-3200S

This BevGuard® brand water filter contains a polyphosphate scale inhibitor and a 0.5 Micron compressed coconut shell carbon block. The scale inhibitor reduces the accumulation of minerals that lead to hard water spots from lime scale build up on equipment. The carbon block provides tremendous capacity to reduce impurities and sediment that may be present in your drinking water. The carbon block has millions of active sites on its surface and within the structure which can absorb impurities like a sponge, and can attract and hold other types of impurities to its surface like a magnet. Additionally, this filter can catalytically breakdown other impurities very similar to the way a catalytic converter works in your automobile. These processes ensure that you are getting the cleanest and best tasting water possible.

This economical filter will provide you with months of protection by reducing hard water build-up in any beverage or food equipment application.

REPLACES:

- **Everpure®:**
4H Filter, 4K Plus, H-100, H-104, MD-CD, OW4-Plus

FILTER FEATURES:

- NSF Certified
- Economical alternative to expensive filter substitutes
- Delivers clean, clear water that looks and tastes great
- Reduces sand, silt, sediment, rust, chlorine taste and odor that may be present in your drinking water
- Designed to provide up to 29,000 gallons of life
- Does not remove minerals which may be beneficial to health

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Micron Rating:	0.5 micron
Dimensions:	16 1/2" x 3 3/16" (41.90 cm x 8.1 cm)
Min Operating Pressure:	25 psi (1.7 bar)
Max Operating Pressure:	125 psi - (8.6 bar)
Operating Temperature:	35-100°F (1.7°C - 38°C)
Flow Rate:	2.1 gpm (7.95 lpm)
Life:	29,000 gallons (109,500 liters)

*Everpure is a registered trademark of Everpure Inc. Northbrook, IL.



المجلس الإسلامي الأمريكي للغذاء و التغذية
THE ISLAMIC FOOD AND NUTRITION COUNCIL OF AMERICA
P.O. BOX 59772 Chicago, IL 60646
Toll Free Phone (877) 425-2523 • Phone: (847) 993-0040 • Fax: (847) 993-0038

IFANCA HALAL PRODUCT CERTIFICATE

Document No.: AQU 17175 17176 220002 US

March 29, 2022

Aquamor, LLC
42188 Rio Nedo
Temecula, California 92563 USA

To Whom It May Concern:

This is to certify that **Aquamor, LLC, Temecula, California, USA** produces **Halal** products under the supervision of the Islamic Food and Nutrition Council of America (IFANCA) in conformity with IFANCA scheme and the following standards:

UAE.S 2055 - 1: 2015

The following products are certified to be **Halal**.

Product Type: Water Treatment Chemicals

Product Code	Product Name
8 52535 00418 9	BevGuard BGE-3200
8 52535 00419 6	BevGuard BGE-3200S
8 52535 00421 9	BevGuard BGE-4200
8 52535 00422 6	BevGuard BGE-4200S

This certificate is valid until **March 31, 2023** and subject to renewal at that time.

Muhammad Munir Chaudry
Muhammad Munir Chaudry, PhD
President



IFANCA Head Office: 2004 Miner St., Des Plaines, IL 60016, USA Tel: 847-993-0034

WWW.IFANCA.ORG

Doc. Number IFANCA-Fm-36 Revision: 2.1 Revision Date/By: 01-18-22/SH Approved Date/By: 01-18-22/MMC Page 1 of 1

L2201





MACES4C-00

Evoca Bean to cups coffee machine

Beant tank

Instant container x3 set

MDB port

Wifi Connect

Touch Screen

Screen Advertising

Optional Vending payless system



LA DECISA 2GR

5 programmable direct selection

buttons for each group

Volumetric dose programming

PID control of boiler temperature

758x589x563mm

58kg

220~240v/3450w

13lt



EVERPURE EV9293-22 COLDRINK /INSURICE TWIN MANIFOLD WITH 20" PREFILTER

Commercial-grade filter head for
Everpure filter cartridges
Includes mounting box
bracket and screws
for fast and easy installation;
no extra
mounting plate is required
Optional built-in water
shut-off valve and
flushing valve makes cartridge
change-outs easy
Cartridge nesting feature
provides a more
secure, durable fit



EVERPURE ® COLDRINK EV9293-21 /INSURICE ® MANIFOLD WITH 20" PREFILTER

Commercial-grade filter head for
Everpure filter cartridges
Includes mounting box bracket
and screws
for fast and easy installation; no
extra
mounting plate is required
Optional built-in water shut-off
valve and
flushing valve makes cartridge
change-outs easy
Cartridge nesting feature
provides a more
secure, durable fit



EVERPURE 4FC-S FILTER CARTRIDGE EV9692-31

Increased capacity for extended
reduction
of chemical and mechanical
contaminants
Balanced cartridge for optimum
performance in varying water qualities
Integrated beaded phosphate with levels
specifically selected for greater life and
scale inhibition





SODA EXPRESS PINACLE SODA MAKER

- New patented fizz infuser to carbonate "any and all liquids"
- Detachable infuser for easy cleaning
- Simple to use Click Press Release steps
- No batteries or external power required
- Creates sparkling water within seconds
- Sleek and modern design

- 1 x PINNACLE Sparkling Water Machine
- 1 x Carbonating Gas Cylinder
- 1 x 1L Carbonating Bottle
- 1 Year Warranty



**Step 1:
CLICK**
Insert the bottle into the dock
& twist bottle until it clicks to lock




**Step 2:
PRESS**
Press the main button once
to carbonate water



**Step 3:
RELEASE**
Press small button to unlock bottle
& remove bottle from dock

HEAT PULL CAN BOTTLE SEALER MACHINE

- Dimension : 635X350X200mm
- Voltage : 220v/50/1/370w
- Seal Can Diameter : 55mm
- Weight : 32kg
- Colour : Black






HEAT WATER BOILER 8L

- Model : HB-8L
- Dimensions: 190x240x490mm
- Power : 220V/50Hz/2500W
- Capacity : 30 Liter
- Micro Computer Control
- Stainless Steel Body
- 304 Stainless Steel inside pot

HEAT WATER BOILER 20L

- Model : HGSK02A
- Dimensions : 365x390x600mm
- Power : 220v/50Hz/3000W/15amps
- Tank Capacity: 20 Liter
- Production :100 Liter / Hour
- 8 minute get 100°C




Vitamix The Quiet One

- Dimensions : 216x295x622mm
- Output Power : 1300-1550W / 10 amps/ 3HP
- 6 pre-set program buttons on touch-pad.
- 1.4 Ltr high-impact, clear/stackable Advance® container, complete with Advance® blade assembly and lid
- Efficient container and blade configuration that can power through various ingredients like frozen fruit, whole fruit and ice with liquid.
- Magnetically sealed sound enclosure.



Touch n go advance

- Dimension : 49.2Hx23.5Wx26.7D cm
- Motor : 2 peak output horsepower
- Electrical : 220-240V, 50/60Hz , 1057-1200w
- Net Weight : 7.7Kg
- The T&G offer reduced sound and blending time. It quickly and easily creates smoothies, frappes, ice cream drinks and frozen cocktails
- 2 Peak out HP motor and sound-reducing cover for superior performance in coffee, smoothie, and ice cream shops.
- 34 Optimized programs engineered to provide consistent results quickly and easily.
- Advance : container creates faster, smoother pouring and has a longer blade life resulting in time and cost savings along with improved customer experience.



Vitamix Prep 3

- Dimensions : 514H x 203W x 229D mm
- Jug Capacity : 2L , Motor Power (Watts) : 2100
- Electrical : 220-240 V, 50 Hz
- Output Power 1100 - 1200 W
- Weight : 5.5kg
- Variable speed and accelerator tool allows for control and easy processing of dense ingredients .
- Advanced cooling fan for optimum reliability during peak hours of operation .
- Patented, high-impact container is clear for seeing ingredients during operation .



Vitamix Drink Machine Advance

- Dimensions : 203x229x450mm
- 2.3 peak output horsepower motor
- 6 Preset program by different timer
- 1.4L Advance Container
- Auto shut off , Heavy Duty
- Tritan Material BPA Free container



Vitamix 2 Speed

- Dimensions : 203x229x514mm
- High and low Speed , 2.0L Tritan Material BPA Free Container



- 2 Peak Hourspower , Heavy Duty





**EJ-306 Sound
proof
285x234x490mm
1500w
220~240v/50hz
8kg
8 program
10 stage
Safty Jug**



**7100 Milk Steamer
Tempeture Setting
214x430x350m
2200w
5L
5 program**




**XSR-5000 Instant Heat Tea Brewer
510x260x758mm
220v/3600w/15a
5L
Touch Screen
Wife connect
Auto wash
30 recipe**

Food Process Equipment





Mirra 300 Y09



Canova 300

Model	Canova 300	Mirra 300 Y09	Palladio 300 Automec
Ø blade	300mm	300mm	300mm
Motor	210Watt - 29Hp	210Watt - 29Hp	275 Watt - 37Hp
Cut thickness	19mm	13mm	30mm
Run of carriage	275mm	285mm	310mm
Hopper	250x275mm	250x275mm	365x270mm
Dimensions (DxWxH) m	640x495x495m	640x610x510mm	685X660X750mm
Net Weight	26Kg	20Kg	55Kg
Gross Weight	29Kg	23Kg	70Kg



Tips for Thinly Slicing Raw Beef



Palladio 300 Automec





Saw blade (in)	77.953" (1980mm)
Blade speed	72.07 ft/sec
Throat width (in)	8.66"
Throat height (in)	12.99"
Table dimensions (WxL)	18.11" x 22.05" (460mm x 560mm)
Switch type	Push Button
Epoxy enamel	Yes
Waste tray	No
Movable blade guard	Yes
Sealed off bearings	Yes
Non slip silent V-belt drive	No
Net weight	60 Kg
Shipping weight/cube	127 Kg / 229 cf
Voltage	220/50/60/1, 220/60/3 or 380/50/3



Motor	1 HP 0.74 kW
Electric	115/60/1 or 220/50/60/1
Grinding capacity first ground	13 Kg/min (28.66 lbs./min) (3/8")
Grinding capacity second ground	6.5 Kg/min (14.33 lbs./min) (1/8")
Pan dimensions (L x W x H)	763.5 mm x 420 mm x 80.9 mm (30.06" x 16.54" x 9.84")
Machine dimensions (L x W x H)	790.1 mm x 420 mm x 521.9 mm (31.11" x 16.54" x 16.62")
Net weight	57 Kg (125.66 lbs)
Shipping weight	74 Kg (163.14 lbs)



Saw blade (Inches)	2950 mm (116.14" x .5/8")
Blade speed	16 m/sec (52.49 ft/sec)
Throat width (Inches)	340 mm (13.39")
Throat height (Inches)	420 mm (16.54")
Table dimensions (WxL)	890 mm x 520 mm (35.04" x 20.47")
Switch type	Thermomagnetic
Finish	Lead-free epoxy enamel very corrosion resistant
Waste tray	Yes
Movable blade guard	Yes
Sealed off bearings	Yes
Non slip silent V-belt drive	Yes
Net weight (Shipping)	173 Kg (211 Kg) 381.4 lbs. (465.18 lbs.)
Voltage	380/50/3



robot coupe®



440 W

MP 350 Ultra

500 W

MP 450 Ultra

750 W

MP 550 Ultra

850 W

MP 600 Ultra

1000 W

MP 800 Turbo

440 W

MP 350 Combi Ultra

500 W

MP 450 Combi Ultra

500 W

MP 450 FW Ultra

MP 350/MP 450;
9500 rpm
MP 350 V.V./MP 450 V.V.:
1500 to 9000 rpm

9000 rpm

9500 rpm


9500 rpm

Mixer : 1500 to 9000 rpm
Whisk : 250 to 1500 rpm

250 to 1500 rpm

LARGE RANGE	Electrical data				Dimensions (in mm)						Weight (kg)	
	Speed (rpm)		Power (Watts)	Voltage* (Amp.)	A	B	C	D	E	F	net	gross
	Mixer	Mixer Variable speed										
MP 350 Ultra	9500		440	230 V/50Hz 2.1	125	725	100	360			4.6	6.1
MP 350 V.V. Ultra		1500 to 9000	440	230 V/50Hz 2.1	125	725	100	360	440	120	4.8	6.3
MP 450 Ultra	9500		500	230 V/50Hz 2.3	125	825	100	460			4.9	6.4
MP 450 V.V. Ultra		1500 to 9000	500	230 V/50Hz 2.3	125	825	100	460	440	120	5.0	6.4
MP 550 Ultra	9000		750	230 V/50Hz 3.5	125	925	111	560			5.2	6.7
MP 600 Ultra	9500		850	230 V/50Hz 3.4	124	970	110	580			5.7	7.6
MP 800 Turbo	9500		1000	230 V/50Hz 4.5	125	1130	110	740			7.1	9

75




Robot Coupe Vegetable Preparation Machine

- Model : CL50
- Dimensions : 375x343x595mm
- Output power : 1119Watt
- Electrical data : Single-phase - 12 Amp plug included
- Speed : 425rpm
- Net Weight : 19Kg



Robot Coupe Vegetable Preparation Machine

- Model : CL52
- Dimensions : 360x340x690mm
- Output power : 750Watt
- Electrical data : 230V/1/50Hz
- Speed : 375rpm
- Net Weight : 22.5Kg





Garlic slicer machine

- Size : W340*L205*H300 (mm)
- Weight : 6.5kg
- Cutting size : selected in between 1~5mm
- Rated Speed : 136rpm
- Rated Output : 110~240V / 50~60Hz / 150W



Scallion Slicer Machine

- Size : W340*L205*H300 (mm)
- Weight : 6.5kg
- Cutting size : selected in between 1~5mm
- Rated Speed : 1,026rpm
- Rated Output : 110~240V / 50~60Hz / 150W



Meat Tenderizer Machine

- Size : W470*L335*H410 (mm)
- Weight : 22kg
- Rated Output : 110~240V / 50~60Hz / 400W



신영 글로벌 (주)
SHIN YOUNG GLOBAL CO.,LTD





Scallion Shredder Machine

- Size : W440*L225*H355 (mm)
- Weight : 15kg
- Cutting Size : Selected in between 2.3mm~9mm
- Rated speed : About 30 scallion/min
- Rated output : 110~240V, 50~60Hz, 300W



Hot Pepper Slicer

- Size : W340*L205*H300 (mm)
- Weight : 6.5kg
- Cutting Size : selected in between 1~7mm
- Rated speed : 280 rpm
- Rated output : 110~240V / 50~60Hz / 150W



신영 글로벌 (주)
SHIN YOUNG GLOBAL CO.,LTD



**Kit da incasso
per ChocoHot One**
Kit for building
ChocoHot One in the counter
14.1.INCASSO



**Kit da incasso
per ChocoHot Two**
Kit for building
ChocoHot Two in the counter
14.1.INCASSO2

DIGITAL LINE



Spray Mini digital
08.1.AMINI



110/220 V



2.7 kW



37 kg



47x34x43h cm



0.5-3.5 bar



max 85°C



600 cc/min

Aspirazione diretta dal contenitore del prodotto
Suction direct from the gelatine containers
Aspiración directa de los recipientese de la gelatina
Aspiration directe à partir des récipients de gélatine
Saugvorgang direkt aus den Gelatinebehältern



Spray Mini digital con serbatoio 2,5 lt
Spray Mini digital with 2.5 L tank
08.1AMINIS



110/220 V



2.7 kW



35 kg



41x30x37h cm



0.5-3.5 bar



max 85°C



600 cc/min



	Dositcream 12.DOSI
	110/220 V
	0.18 kW
	27 kg
	45x30x33h cm 45x30x63h cm (8.5 L) 45x30x73h cm (13 L)



	Dositcream-2 12.DOSI2
	110/220 V
	0.36 kW
	41 kg
	53x43x30h cm 53x43x65h cm (8.5 L)



	Dositcream-3 12.DOSI3
	110/220 V
	0.54 kW
	69 kg
	76x43x30h cm 76x43x65h cm (8.5 L)

R O D R O C E S S O R S H R A


DESSERT & SNACK



Heat Soft Ice Cream Maker Machine

- Dimensions : 540x 730x 800H mm,
- Electrical data : 220v/ 50hz
- Output power : 2300w
- Weight : 96kg
- 16-22L/ h , Stainless Steel
- Refrigeration tank : 1.6L x 2
- Storage tank : 4.3L x 2
- Touch screen , Fast and easy to operate during peak hours.

Model:HCKX-100





i-on 16 AP

Soft Serve

Remote Access and 7” wide touch screen display for promotional videos and photos

With our new i-on models you are able to have full control and remote access to the machine via any smart phone, tablet or a computer from anywhere, quickly, easily and reliably.



EFE 1600 A

Soft Serve – Frozen Yoghurt

Special agitator design to keep the hopper mix homogenized all the time.



i-on 40 AP

Soft Serve

Remote Access and 7” wide touch screen display for promotional videos and photos

With our new i-on models you are able to have full control and remote access to the machine via any smart phone, tablet or a computer from anywhere, quickly, easily and reliably.



EFE 4000

Soft Serve

Model with three head, without pump and high capacity, wheeled

SHORT TERM LEASING





Ice Cream Maker Machine

- Dimensions : 540x 730x 800H mm,
- Electrical data : 220v/ 50hz
- Output power : 2300w
- Weight : 96kg
- 16-22L/ h , Stainless Steel
- Refrigeration tank : 1.6L x 2
- Storage tank : 4.3L x 2
- Touch screen , Fast and easy to operate during peak hours.



Chocolate Flavor

This ice cream was rich, creamy, and packed with strong, chocolate notes. The intense flavor hit all the marks on the cocoa radar.



Vallina Flavor

This ice cream was soft, fluffy texture, high-quality taste. Overall, this ice cream was irresistible.



Yogurt Flavor

When comparing yogurt to ice cream, you have to throw in the health benefits here too because yogurt is technically healthier than ice cream.



Digital Hood Type Dishwashers

- *AISI 304 stainless steel body, digital control panel
- *Instant display of tank and boiler water temperatures
- *5 different washing programs, adjustable to 60-90-120-180-240 seconds
- *1 dishwashing basket with 3 liters water consumption
- *EPDM rubber hose assembly conforming to Food Codex standards
- *Effective washing results with a specially-designed washing and rinsing arms structure
- *Optional drain pump
- *Optional rinse and detergent dosing pump
- *Thanks to a specially-designed card technology, the rising process does not start before the boiler water temperature reaches 85°C. This guarantees hygienic rinsing according to HACCP standards
- *The washing program can continue when the hood is open and closed
- *9kW boiler heating element, 4.5kW tank heating element
- *Front cover allows easy technical service without moving /dragging the product around
- *Production of adjustable electrical circuit according to different voltages and number of phases



*Model: CRWD500TP

*Dimensions : 590x605x840mm / Basket Dimensions : 500x500mm

*Capacity : 30Basket / hour

*Weight : 61Kg

*Electical Connection : 230v/50Hz

*Total Power : 5.2Kw

*Tank Heating Element : 3.0Kw

*Boiler Heating Element : 4.5Kw


*Wash Pump Power : 0.65Kw

*Tank Capacity : 17Liters / Basket Plate Capacity : 18

*Boiler Capacity : 6.2Liters

*Washing Water Temp : 55C / Rinsing Water Temp : 85C


*Package Dimensions : 600x700x950mm







Stainless Steel Design





We are truly grateful to you for choosing us as your service provider and giving us the opportunity to grow.

None of our achievements would have been possible without you and your unwavering support !!!

Looking forward To serve you And Your Esteemed company

Thank You • Terima Kasih • 谢谢 • 宥 j ń • ありがとう • 감사합니다 • Merci • Spasibo

For more information on Heat Kitchen Equipment Products contact :

Office : +603-92265215 Tel : +6017-357 9281 / +6010-656 9281

Email : sale1@heatkitchenequipment.com / sales2@heatkitchenequipment.com

Website : www.heatkitchenequipment.com



Scan me