

6220E

SOFTSERVEFREEZER

Single flavor, Tabletop, Gravity feed



Most **Compact** & **Versatile** single flavor tabletop model that offers quality, capacity and simplicity

Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

Overrun & Consistency Control

Simple and easy control of viscosity and overrun to ensure product consistency

Low Mix Indicator Light turns "ON" at low mix to alert operator to add mix

Self Closing Dispensing Valve

Automatically prevents product overflow after dispense

Dispense Speed Control

Provides flexibility in dispense rate control for different applications

Ideal for any business with limited counter space

to add ice cream, frozen yogurt, gelato or sorbet.

Simple control makes it super easy to operate.

Great fit for restaurants, bars, kitchens,

convenience stores and delis.

SPACEMAN ICE SYSTEMS (HK) CO, LIMITED

FACTORY: 1 GUANZE RD, INDUSTRY PARK, DAIXI TOWN, HUZHOU, ZHEJIANG, CHINA 313023



Independent hopper cooling system consistently maintains product tempearture below 4°C at all times

Soft Sysetm Start

Slow motor start reduces equipment noise and stress on drive train

Standby

Maintains product temperature in both mix hopper and freezing cylinder below 4°C overnight

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating





PHONE: +86 572 3826788 FAX: +86 572 3826755 Email: info@spaceman-company.com www.spaceman-company.com



6220E

SOFT SERVE FREEZER





FEATURES Control System

Standby Mode

Refrigerated Hopper

Low Mix Indicator Light

SPECIFICATIONS	
Flavors	

Flavors	1
Freezing Cylinders	1 x 1.7L / 1.8qt
Mix Hoppers	1 x 8.0L / 8.5qt
Output Capacity (80 grams)	200 serves/hr
Clearance Requirements	152mm/6" on right

Weight	Kg/lb (Gravity)	
Net	92/203	
Shipping	102/225	
Volume	0.33 CBM / 11.47 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	421/16.6	480 / 18.9
Depth	604/23.8	760/29.9
Height	745 / 29.3	890/35.0

Electrical	MFS	MCA	Power(kW)
220-240/50/1	15	10	1.8
208-230/60/1	15	10	1.8

	0	
	Thermal Overload Protection	\checkmark
	Inverter Soft Start	

Auto Clsoing Dispensing Valve Dispensing Speed Control

Low Temperature Protection

High Pressure Protection

AVAILABLE OPTIONS	
Water Cooled	
Cart (Trolley)	

Single, Analog

 \checkmark

 $\overline{\mathbf{v}}$

 \checkmark

 $\boldsymbol{\cdot}$ Above specifications are subject to change without notice

SPACEMAN USA 224 Commerce St. Unit

224 Commerce St. Unit A1, Broomfield, CO 80020 PHONE: +01 720-328-1020 FAX: +01 720-528-8113 Email: sales@spacemanusa.com www.spacemanusa.com