

Heavy duty commercial induction wok

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)	Capacity (L)
	L	W	H				
LT-D550	750	850	800+400	8-15	380	50/60	18
LT-D600	800	900	800+400	12	380	50/60	23
LT-D700	900	1100	800+400	15	380	50/60	40
LT-D800	1000	1100	800+400	20	380	50/60	60
LT-D900	1100	1200	800+400	25	380	50/60	80
LT-D1000	1200	1300	800+400	30	380	50/60	110
LT-D1200	1400	1500	800+400	30-40	380	50/60	180

Single commercial induction wok

LT-D550	750	850	800+400	8-15	380	50/60	18
LT-D600	800	900	800+400	12	380	50/60	23
LT-D700	900	1100	800+400	15	380	50/60	40
LT-D800	1000	1100	800+400	20	380	50/60	60
LT-D900	1100	1200	800+400	25	380	50/60	80
LT-D1000	1200	1300	800+400	30	380	50/60	110
LT-D1200	1400	1500	800+400	30-40	380	50/60	180

Double commercial induction wok

LT-D550II	1500	850	800+400	2x(8-15)	380	50/60	18X2
LT-D600II	1600	900	800+400	2X12	380	50/60	23X2
LT-D700II	1800	1100	800+400	2X15	380	50/60	40X2
LT-D800II	2000	1100	800+400	2X20	380	50/60	60X2
LT-D900II	2200	1200	800+400	2X25	380	50/60	80X2
LT-D1000II	2400	1300	800+400	2X30	380	50/60	110X2

Commercial induction wok with pot

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)	Heating diameter (mm)
	L	W	H				

Single commercial induction wok

LT-X300	700	750	800+400	8	380	50/60	Φ250
LT-X400	750	850	800+400	8-18	380	50/60	Φ330
LT-X500	850	950	800+400	12-20	380	50/60	Φ400

Single commercial induction wok with sink

LT-X300	1000	1000	800+400	8	380	50/60	Φ250
LT-X400	1050	1100	800+400	8-18	380	50/60	Φ330
LT-X500	1150	1200	800+400	12-20	380	50/60	Φ400

Double commercial induction wok with sink

LT-X300II	1600	1000	800+400	2x8	380	50/60	Φ250
LT-X400II	1800	1100	800+400	2x(8-18)	380	50/60	Φ330
LT-X500II	2000	1200	800+400	2x(12-20)	380	50/60	Φ400

Double commercial induction wok with sinks

LT-X300II	1900	1000	800+400	2x8	380	50/60	Φ250
LT-X400II	2000	1100	800+400	2x(8-18)	380	50/60	Φ330
LT-X500II	2200	1200	800+400	2x(12-20)	380	50/60	Φ400

Automatic commercial induction soup cooker

Model	Size(L*W*H)mm						Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H	Barrel Diameter	Barrel height	Capacity (L)			
LT-Y700	900	1100	800+400	650	520	170	15-25	380	50/60
LT-Y800	1000	1100	800+400	750	520	230	20-30	380	50/60
LT-Y900	1100	1200	800+400	850	520	290	20-30	380	50/60
LT-Y1000	1200	1300	800+400	950	520	360	25-35	380	50/60

Induction Flat Cooker

Model	Glass size (mm)	Heating diameter (mm)	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
			L	W	H			

Single flat commercial induction soup cooker

LT-P420	Φ430	Φ340	650	700	550+650	8	380	50/60
						12		
						15		
						18		

Double flat commercial induction soup cooker

LT-P420II	Φ430	Φ340	1300	700	550+650	2x8	380	50/60
						2x12		
						2x15		
						2x18		

Commercial induction dimsum steamer

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			
LT-LTL	750	1100	800+400	12	380	50/60
				15		
				18		
				20		

Commercial induction rice roll steamer

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			
LT-CFII	950	900	800+400	15	380	50/60
				18		50/60
				20		50/60

Cabinet commercial induction steamer

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			

Cabinet commercial induction seafood steamer

LT-HI	1000	900	1860	20-45	380	50/60
-------	------	-----	------	-------	-----	-------

Cabinet commercial induction rice steamer

LT-Z12	850	800	1890 (Single door)	12-45	380	50/60
LT-Z12	1150	900	1400 (Double door)		380	50/60
LT-Z24	1150	900	1890 (Double door)		380	50/60
LT-Z36	1550	1100	1650 (Double door)		380	50/60
LT-Z48	1550	1100	1890 (Double door)		380	50/60

Commercial induction stew soup cooker

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			
LT-PDZ500	750	850	800+400	12/15	380	50/60
LT-PDZ600	800	900	800+400	12/15	380	50/60
LT-PDZ700	900	1000	800+400	12/15	380	50/60
LT-PDZ800	1000	1100	800+400	12/15/20	380	50/60

Nine-holes Commercial induction pasta cooker

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			
LT-TMIX	700	800	800+150	12	380	50/60
				15		50/60

Six-holes automatic commercial induction pasta cooker

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			
LT-TMVI	600	800	800+150	12	380	50/60
				15		50/60

Commercial induction griddle

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			
LT-PL	700	800	800+150	8	380	50/60
				10		
				12		

Commercial induction teppanyaki griddle

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			
LT-TB	1400	800	800+125	8	380	50/60
				10		
				12		

Commercial induction deep fryer

Model	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
	L	W	H			
LT-ZLII	450	800	800+150	8	380	50/60
				10		50/60
				12		50/60

Commercial induction ranges

Model	Glass size (mm)	Heating diameter (mm)	Size(L*W*H)mm			Power (kW)	Voltage (V)	Frequency (Hz)
			L	W	H			

Four burners commercial induction range

LT-B300IV	Φ300	Φ210	700	800	800+150 Cabinet/Shelf	4X3.5 4X5	220/380	50/60
LT-TBZ 300IV	Φ300	Φ210	700	800	330 Desktop	4X3.5 4X5	220/380	50/60

Six burners commercial induction range

LT-B300VI	Φ300	Φ210	1050	800	800+150 Cabinet/Shelf	6X3.5 6X5	220/380	50/60
LT-TBZ 300VI	Φ300	Φ210	1050	800	330 Desktop	6X3.5 6X5	220/380	50/60



Portable tabletop induction cooktops

Model	Size(L*W*H)mm			Power (kw)	Voltage (v)	Frequency (hz)
	L	W	H			

Thin tabletop induction cooktop

LT-TAM-A135	370	455	180	3.5	220	50
-------------	-----	-----	-----	-----	-----	----

Portable induction wok cooktop

LT-C35-L	340	410	110	3.5	220	50
----------	-----	-----	-----	-----	-----	----



Mid tabletop induction cooker

Model	Size(L*W*H)mm			Power (kw)	Voltage (v)	Frequency (hz)
	L	W	H			

Tabletop induction wok cooker

LT-TAM-B135	420	470+50	240	3.5	220	50
LT-TAM-B105				5		50

Tabletop induction cooker

LT-TPM-B135	420	470+50	180	3.5	220	50
LT-TPM-B105				5		50



Large tabletop induction cooker

Model	Size(L*W*H)mm			Power (kw)	Voltage (v)	Frequency (hz)
	L	W	H			

Tabletop induction wok cooker

LT-TAM-B535	520	570+50	308	3.5	220	50
LT-TAM-B505				5		50
LT-TAM-E105				5		50
LT-TAM-E108				8	380	50
LT-TAM-E112				12		50

Tabletop induction cooker

LT-TPM-S35	520	570+50	250	3.5	220	50
LT-TPM-B505				5		50
LT-TPM-E105				5		50
LT-TPM-E108				8	380	50
LT-TPM-E112				12		50



Built-in induction cooktop

Model	Size(L*W*H)mm			Power (kw)	Voltage (v)	Frequency (hz)	Glass Size (MM)	Countertop opening size (MM)
	L	W	H					

Built-in induction wok

LT-QAM C135/C105	400	400	238	3.5-5	220	50	Φ300	385×385
LT-QAM F305/F308	500	500	280	5-8	380	50	Φ400	485×485

Built-in induction cooker (steel around)

LT-QPM C135/C105	400	400	200	3.5-5	220	50	330X330	385X385
LT-QPM F105/F108	460	460	200	5-8	380	50	330X330	445X445

Built-in induction cooker (Full glass ceramic)

LT-QPM C335/C205	345	345	136	3.5-5	220	50	345X345	320X320
LT-QPM F205/F208	460	460	200	5-8	380	50	460X460	435X435

Remark: The installation environment of Embedded Desktop Induction Cooker must be well ventilated, otherwise it may cause malfunction due to poor heat dissipation during long-term work.



Tabletop induction deep fryer

Model	Size(L*W*H)mm			Power (kw)	Voltage (v)	Frequency (hz)
	L	W	H			
LT-TZL-B135	450	530	300+100	3.5	220	50
LT-TZL-B105				5		50



Tabletop induction griddle

Model	Size(L*W*H)mm			Power (kw)	Voltage (v)	Frequency (hz)
	L	W	H			
LT-TPL-B135	550	530	300+100	3.5	220	50
LT-TPL-B105				5		50



Tabletop induction pasta cooker

Model	Size(L*W*H)mm			Power (kw)	Voltage (v)	Frequency (hz)
	L	W	H			
LT-TMIV-B135	450	530	300+100	3.5	220	50
LT-TMIV-B105				5		50

Lestov Commercial Induction Cooker(Accessories)



Lestov Commercial induction cooker characteristics

- ★ High efficiency, low noise, no pollution
- ★ Use national patent coil, more uniform firepower
- ★ PCB Box with fully sealed design
- ★ Handle type magnetic switch design for 8 gears firepower
- ★ Triple three-dimensional radiation shielding design
- ★ Use advanced Germany "Infineon IGBT technology"
- ★ IPX4 protection level of multiple security